


Lux Fire 70mm cut-out IP65 Fire Rated Downlight 12W (61W) 3000K 850lm 55 deg beam angle Dimmable

Partcode: ILDLFR70A009 / Page: 1



As LED products produced using new technologies are used with old dimmer technology, achieving effective and smooth dimming can be challenging. For this dimmable downlight we have tested, and recommend, the dimmer detailed in the specification below.

**** Awarded 4 Stars "Recommended" by Lux Review (January 2016) ****

Who says you can't have style without safety? Integral LED Lux Fire downlights not only conform to 30, 60 and 90mins fire rating specifications but are also rated to IP65, so they can be used safely in bathrooms. Lux Fire fire-rated downlights have been tailored to deliver a premium finish to any home or business with their low-glare, high-quality light and contemporary design that looks impressive in any setting.

Lux Fire downlights are built using a deep recessed COB LED light source, providing a beam that has softened edges for a luxurious effect. Supplied with a white scalloped metal bezel (interchangeable). Easy to install with low-profile body. Complete with Loop-in / Loop-out driver. IP65 and Air tightness compliant with Part C and Part L. Resistance to Sound compliant with Part E.

Product Details

Partcode: ILDLFR70A009

Check Code: 694707

Range Name: Lux Fire

Placement / Application: Indoor, General Lighting

Market Segment: Commercial indoor, Residential indoor

Product Type: Fire Rated

Warranty: 3 Years

CE / RoHS: Yes

Physical Data

Product Finish: Matt white

Spot Type: COB

Optic: Clear Refractor

Material: Aluminium alloy, Acrylic, Iron, Intumescent material

Construction: Extruded Aluminium alloy heat-sink, Iron body, Steel springs and mounting plate, Acrylic diffuser

Physical Data

Length: 70mm
Diameter: 85mm
Weight (Unpackaged Single Unit): 370g
Cut Out Diameter: 70mm
Luminaire Fixing: Recess mounted
Fire Rating: 30, 60, 90


Electrical Data

Voltage Range: 220-240V
Power Consumption: 12.0 Watts
Driver included: Yes
Electric Current: AC
Ampage: 240.00mA
Frequency Range: 50/60 Hz
Power Factor: ≥ 0.89
Wattage Equivalent: 61 Watts
Dimming: Dimmable with compatible dimmers
Compatible Dimmer(s): Varilight JQP401W
LVD Certified: Yes
EN: EN-60598

Light Data

Lumens: 850lm
Lumens per Watt: 71.0lm/W
Beam Angle: 55°
Correlated Colour Temperature (CCT): 3000k
Colour Temperature: Warm White
Colour Rendering Index (CRI): ≥ 80
LED Type: Chip on board (COB)
Instant on - Less than 1 second: Yes
Lifetime: 35,000 hrs
Switching Cycles: $>17,500$ X

Environmental



Lowest Operating Temperature: -20 degrees
Maximum Operating Temperature: 45 degrees
IP (Ingress Protection) Rating: IP65
Hg 0% (Mercury Free): Yes

Packaging



EAN Barcode (unit of 1): 5055788213796
Packaged Weight (Unit of 1): 410g
Length (unit of 1): 140mm
Width (unit of 1): 110mm
Depth (unit of 1): 95mm
Outer packaging info available on website

Product data last updated on: Wednesday, June 5, 2019 - 17:02